

# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/576,920	05/23/2000	Kazuhiro Okanoue	11605A	3444	
23389 7	7590 11/05/2004		EXAMINER		
SCULLY SCOTT MURPHY & PRESSER, PC 400 GARDEN CITY PLAZA			RYMAN, I	RYMAN, DANIEL J	
GARDEN CITY, NY 11530		,	ART UNIT	PAPER NUMBER	
	•	•	2665		

DATE MAILED: 11/05/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

•	Application No.	Applicant(s)				
Office Action Summan	09/576,920	OKANOUE ET AL.				
Office Action Summary	Examiner	Art Unit				
	Daniel J. Ryman	2665				
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the co	orrespondence address				
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.  - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.  - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).						
Status						
1)⊠ . Responsive to communication(s) filed on 09 Se	1) Responsive to communication(s) filed on <u>09 September 2004</u> .					
2a) ☐ This action is <b>FINAL</b> . 2b) ☒ This	This action is <b>FINAL</b> . 2b)⊠ This action is non-final.					
3) Since this application is in condition for allowan	Since this application is in condition for allowance except for formal matters, prosecution as to the ments is					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4) Claim(s) 1-10 and 15 is/are pending in the application.						
	4a) Of the above claim(s) <u>15</u> is/are withdrawn from consideration.					
5) Claim(s) is/are allowed.						
	) Claim(s) <u>1-3,5-7,and 9</u> is/are rejected.					
· <u> </u>	Claim(s) 4,8 and 10 is/are objected to.					
8) Claim(s) are subject to restriction and/or	election requirement.					
Application Papers						
9) The specification is objected to by the Examiner.						
10) ☐ The drawing(s) filed on is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).  11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>						
Attachment(s)						
1) Notice of References Cited (PTO-892)  4) Interview Summary (PTO-413)						
2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(s)/Mail Da	te				
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date	6) Other:	atent Application (PTO-152)				

Art Unit: 2665

#### **DETAILED ACTION**

## Response to Arguments

- 1. Applicant's arguments filed 9/9/04 have been fully considered but they are not persuasive. On page 27 of the Response, Applicant argues that "Brewer does not disclose or suggest a mobile terminal that detects whether the mobile has moved from the network." However, Applicant recognizes that in Brewer the user dictates to the mobile terminal that it is in a new network. The limitation of claim 1 only requires that the move manager in the mobile terminal detect whether the mobile terminal has moved. The limitation does not specify how this detection occurs. Therefore, Examiner asserts that, as broadly defined, Brewer discloses a move manager that detects whether the mobile terminal has moved where the detection is based on an input from the user.
- 2. Examiner notes that Applicant implies that the detection must occur automatically. However, it is obvious to one of ordinary skill in the art to automate a manual activity. MPEP § 2144.04(III). Since Brewer discloses that the detection occurs through a manual process, it would have been obvious to have the mobile terminal automatically detect whether the mobile terminal has moved.
- 3. On page 29, Applicant argues that there is "no motivation for combining Brewer and Sharony as suggested by the Examiner." In response to applicant's argument that there is no suggestion to combine the references, Examiner recognizes that obviousness can only be established by combining or modifying the teachings of the prior art to produce the claimed invention where there is some teaching, suggestion, or motivation to do so found either in the references themselves or in the knowledge generally available to one of ordinary skill in the art.

See In re Fine, 837 F.2d 1071, 5 USPQ2d 1596 (Fed. Cir. 1988) and In re Jones, 958 F.2d 347, 21 USPQ2d 1941 (Fed. Cir. 1992). In this case, while Brewer does not expressly disclose that the second network can be an ad hoc network where an ad hoc network is a temporary network formed of only plural terminals, Brewer does disclose that the second network can be wireless (col. 5, line 47-col. 6, line 21); that the second network can be of various configurations and types (col. 6, lines 22-39); and that the second network needs only to have the ability to transmit a terminal address (IP address) and network address (subnet mask) to a newly connected computer (col. 8, lines 12-37). Sharony teaches, in an ad hoc network (network with dynamically changing topology), that an ad hoc network has the ability to transmit a terminal address and network address to a newly connected computer in order to provide a network where nodes can change network affiliation dynamically (col. 2, lines 9-26; col. 5, line 36-col. 6, line 14; and col. 6, lines 33-44), where the ad hoc network is a network temporarily formed of only plural terminals (col. 1, lines 18-23). Thus, Examiner maintains that it would have been obvious to one of ordinary skill in the art at the time of the invention to use an ad hoc network as the second network in order to allow mobile terminals to be able to dynamically enter and leave a network in which a wired backbone does not exist. With the motivation being an ad hoc network allows for a dynamic architecture.

- 4. Given the above arguments, Examiner maintains the rejection of claims 1-7 and 9.
- 5. If Applicant does not traverse the Examiner's assertion of official notice or Applicant's traverse is not adequate, then the common knowledge or well-known in the art statement is taken to be admitted prior art because Applicant failed to traverse the Examiner's assertion of official notice or that the traverse was inadequate (see MPEP §2144.03(c)).

Art Unit: 2665

Election/Restrictions

6. Newly submitted claim 15 is directed to an invention that is independent or distinct from the invention originally claimed. Claim 15 is directed to a mobile terminal which connects to an ad hoc network through another terminal having the shortest connection time. Claims 1-10 are directed to a mobile terminal which connects to an ad hoc or a infrastructure network. Therefore claim 15 and claims 1-10 are independent since these claim 15 and claims 1-10 have separate utility.

Since applicant has received an action on the merits for the originally presented invention, this invention has been constructively elected by original presentation for prosecution on the merits. Accordingly, claim 15 is withdrawn from consideration as being directed to a non-elected invention. See 37 CFR 1.142(b) and MPEP § 821.03.

### Claim Rejections - 35 USC § 103

- 7. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 8. Claims 1-3, 5-7, and 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Brewer et al (USPN 5,918,016) in view of Sharony (USPN 5,652,751).
- 9. Regarding claim 1, Brewer discloses a mobile terminal that can be connected in a mobile mode between an infrastructure network and an second network (col. 4, lines 27-62), said infrastructure network being a permanent network interconnected via a relay node (col. 5, line 47-col. 6, line 64 and col. 7, lines 20-58), said second network being a network formed of plural

terminals (col. 5, line 47-col. 6, line 64 and col. 8, line 37-col. 9, line 35), said infrastructure network having plural mobile terminals, relay nodes, and a server which provides information needed for connection of mobile terminals (col. 5, line 47-col. 6, line 64 and col. 8, line 37-col. 9, line 35); and wherein an infrastructure network connection procedure and an second network connection procedure are configured in an integrated mode in an address management process (col. 4, lines 28-62), a connection network identification process (col. 9, lines 21-35) and a destination address capture process which are needed when said mobile terminal is connected to a network to establish communications (col. 11, lines 45-56) where "an IP address of one or more machines providing name services" is taken to indicate a destination address capture process; wherein each process including steps of identifying whether a network to which said mobile terminal is connected is a second network or infrastructure network and then using a procedure corresponding to the connected network (col. 4, lines 27-62 and col. 9, lines 21-35); and wherein a move manager detects whether the mobile terminal is moved from at least one of the ad hoc network and the infrastructure network (col. 12, line 55-col. 13, line 12).

Brewer does not expressly disclose that the second network can be an ad hoc network where an ad hoc network is a temporary network formed of only plural terminals. Brewer does disclose that the second network can be wireless (col. 5, line 47-col. 6, line 21); that the second network can be of various configurations and types (col. 6, lines 22-39); and that the second network needs only to have the ability to transmit a terminal address (IP address) and network address (subnet mask) to a newly connected computer (col. 8, lines 12-37). Sharony teaches, in an ad hoc network (network with dynamically changing topology), that an ad hoc network has the ability to transmit a terminal address and network address to a newly connected computer in

order to provide a network where nodes can change network affiliation dynamically (col. 2, lines 9-26; col. 5, line 36-col. 6, line 14; and col. 6, lines 33-44), where the ad hoc network is a network temporarily formed of only plural terminals (col. 1, lines 18-23). It would have been obvious to one of ordinary skill in the art at the time of the invention to use an ad hoc network as the second network in order to allow mobile terminals to be able to dynamically enter and leave a network in which a wired backbone does not exist.

10. Regarding claim 2, Brewer discloses a mobile terminal that can be connected in a mobile mode between an infrastructure network and a second network (col. 4, lines 27-62), said infrastructure network being a permanent network interconnected via a relay node (col. 5, line 47-col. 6, line 64 and col. 7, lines 20-58), said second network being a network formed of plural terminals (col. 5, line 47-col. 6, line 64 and col. 8, line 37-col. 9, line 35), said infrastructure network having plural mobile terminals, relay nodes, and a server which provides information needed for connection of mobile terminals (col. 5, line 47-col. 6, line 64 and col. 8, line 37-col. 9, line 35), said mobile terminal comprising: a. receive packet input means for inputting as a receive packet a packet transmitted onto a communication medium configuring a network to be connected (col. 9, lines 21-35); b. transmission packet output means for transmitting a transmission packet onto said communication medium (col. 9, lines 21-35); c. means for inputting an opposite communication party's name of said mobile terminal itself (col. 11, lines 45-56) where it is implicit from "an IP address of one or more machines providing name services" that there is a means for inputting an opposite communication party's name; d. means for outputting a destination address corresponding to said opposite communication party's name (col. 11, lines 45-56) where it is implicit that communication in the network occurs through

destination addresses such that a destination addresses is output corresponding to the opposite communication party's name when the device issues a packet for the opposite party; e. address management means for receiving said receive signal, for identifying whether or not said network to be connected is said infrastructure network or a second network, and for transmitting said transmission packet which captures and manages an address used in said network (col. 4, lines 27-62; col. 8, lines 12-37; and col. 9, lines 21-35); f. destination address capture means for receiving said receive signal, for identifying whether or not said network to be connected is said infrastructure network or ad hoc network, for outputting said transmission packet to capture said destination address corresponding to said opposite communication party's name, and for obtaining a destination address of said opposite communication party's name (col. 4, lines 27-62; col. 8, lines 12-37; col. 9, lines 21-35; and col. 11, lines 45-56) where "an IP address of one or more machines providing name services" is taken to indicate a destination address capture process; and g. move management means for receiving said receive packet and outputting said transmission packet to manage whether or not said movable terminal itself has moved from said network to be connected to another network (col. 12, line 55-col. 13, line 12).

Brewer does not expressly disclose that the second network can be an ad hoc network where an ad hoc network is a temporary network formed of only plural terminals. Brewer does disclose that the second network can be wireless (col. 5, line 47-col. 6, line 21); that the second network can be of various configurations and types (col. 6, lines 22-39); and that the second network needs only to have the ability to transmit a terminal address (IP address) and network address (subnet mask) to a newly connected computer (col. 8, lines 12-37). Sharony teaches, in an ad hoc network (network with dynamically changing topology), that an ad hoc network has

Application/Control Number: 09/576,920

Art Unit: 2665

the ability to transmit a terminal address and network address to a newly connected computer in order to provide a network where nodes can change network affiliation dynamically (col. 2, lines 9-26; col. 5, line 36-col. 6, line 14; and col. 6, lines 33-44), where the ad hoc network is a network temporarily formed of only plural terminals (col. 1, lines 18-23). It would have been obvious to one of ordinary skill in the art at the time of the invention to use an ad hoc network as the second network in order to allow mobile terminals to be able to dynamically enter and leave a network in which a wired backbone does not exist.

Page 8

11. Regarding claim 3, referring to claim 2, Brewer in view of Sharony discloses that the address management means comprises: a. ad hoc/ infrastructure network identification means for identifying whether or not a network to be connected by said mobile terminal itself is said infrastructure network or said ad hoc network in response to said receive packet (Brewer: col. 9, lines 21-35 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44), for outputting a network identification signal representing a network to which a network to be connected by said mobile terminal itself is connected, for outputting an infrastructure network connection signal when said network to be connected is said infrastructure network, and for outputting an ad hoc network connection signal when said network to be connected is said ad hoc network (Brewer: col. 9, lines 21-35 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where it is implicit that the device will notify all parts within the device as to in which network the device is operating; b. infrastructure network address management means for receiving said receive packet and said infrastructure network connection signal, for outputting necessary transmission data as said transmission packet, and for managing an address used by said mobile terminal itself when a network to be connected by said mobile terminal itself is an infrastructure network (Brewer: col.

Application/Control Number: 09/576,920

Art Unit: 2665

9, lines 21-35); c. ad hoc network address management means for receiving said receive packet and said ad hoc network connection signal, for outputting necessary data as said transmission packet, and for managing an address used by said mobile terminal itself when said network to be connected by said mobile terminal itself is an ad hoc network (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44); and d. a switch for receiving said network identification signal, said transmission packet from said infrastructure network address management means, and said transmission packet from said ad hoc network address management means, for selectively outputting said transmission packet from said infrastructure network address management means by said network identification signal when a network in a connection state to said mobile terminal itself is an infrastructure network, and for selectively outputting said transmission packet from said ad hoc network address management means when said network in a connection state is an ad hoc network (Brewer: col. 4, lines 27-62; col. 8, lines 12-37; and col. 9, lines 21-35 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44).

Page 9

12. Regarding claim 5, referring to claim 3, Brewer in view of Sharony discloses that the ad hoc network address management means comprises: a. ad hoc network/ network address management means for receiving said receive packet and said ad hoc network connection signal, outputting a message requesting a network address containing a network address used in a new ad hoc network when a new ad hoc network is configured for connection as said transmission packet (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) and a message representing a spent network address when said ad hoc network/ network address request message containing said spent network address in an ad hoc network connected by said mobile terminal itself has been received (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44)

Application/Control Number: 09/576,920

Art Unit: 2665

where neighbor nodes transmit messages concerning addresses availability/unavailability, capturing a network address of an ad hoc network to which said mobile terminal itself is connected, based on said receive packet (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44), outputting a network address captured signal representing that the captured network address and the network address have been captured, and managing said captured network address not to be used in an overlap mode (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44); and b. an hoc network/ terminal address management means for receiving said receive packet, said ad hoc network connection signal, said captured network address, and said network address captured signal, outputting as said transmission packet a message requesting a terminal address list being used in said ad hoc network when said mobile terminal is connected to an existing ad hoc network and a message containing said terminal address list held by said mobile terminal itself in response to said address list requesting message (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-64), capturing a terminal address used in ad hoc network to be connected by said mobile terminal itself, based on said receive packet and said ad hoc network connection signal, and acknowledging a terminal address to be used in said ad hoc network connected by said mobile terminal itself (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, line 33-col. 7, line 9).

Page 10

13. Regarding claim 6, referring to claim 2, Brewer in view of Sharony discloses that the destination address capture means comprises: a. ad hoc/infrastructure network identification means for receiving said receive packet, identifying whether or not a network to which said mobile terminal is connected is said infrastructure network or said ad hoc network (Brewer: col. 9, lines 21-35 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44), outputting a

network identification signal representing a network to be connected to a network connected by said mobile terminal (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44), outputting an infrastructure network connection signal when said network to be connected is said infrastructure network, and outputting an ad hoc network connection signal when said network to be connected is said ad hoc network (Brewer: col. 9, lines 21-35 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where it is implicit that the device will notify its constituent parts as to which network it is currently connected; b. a first switch for receiving the name of said opposite communication party's name of said mobile terminal itself and said network identification signal and selecting a destination of said opposite communication party's name based on said network identification signal (Brewer: col. 11, lines 45-56 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44); c. infrastructure network/ destination address capture means for receiving said infrastructure network connection signal and said opposite communication party's name, transmitting a message requesting a terminal address corresponding to said communication opponent's name, detecting a message containing a terminal address corresponding to said opposite communication party's name from said receive packet, and outputting said terminal address corresponding to said opposite communication party's name (Brewer: col. 11, lines 45-56); d. ad hoc network/ destination address capture means for receiving said ad hoc network connection signal and said opposite communication party's name, transmitting a message requesting a terminal address corresponding to said opposite communication party's name, detecting a message containing a terminal address corresponding to said opposite communication party's name from said receive packet, and outputting said terminal address corresponding to said opposite communication party's name (Sharony: col. 5,

Art Unit: 2665

line 36-col. 6, line 14 and col. 6, lines 33-44); e. a second switch for selectively outputting a terminal address corresponding to said opposite communication party's name captured by said infrastructure network/ destination address capture means and a terminal address corresponding to said opposite communication party's name captured by said ad hoc network/ destination address capture means, based on said network identification signal (Brewer: col. 11, lines 45-56 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44); and f. a third switch for selectively transmitting a message requesting a terminal address corresponding to said opposite communication party's name captured by said infrastructure network/ destination address capture means and a message requesting a terminal address corresponding to said opposite communication party's name captured by said ad hoc/ destination address capture means, based on said network identification signal (Brewer: col. 11, lines 45-56 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44).

14. Regarding claim 7, referring to claim 6, Brewer in view of Sharony discloses that the ad hoc network/destination address capture means comprises: a. destination terminal address detection means for receiving said network identification signal, starting up when a connection network of said mobile terminal itself is an ad hoc network, receiving said receive packet and said opposite communication party's name, outputting the terminal address of said opposite communication party's name by detecting a destination address message containing correspondence relationships between said opposite communication party's name and said opposite communication party's terminal address from said receive packet, and outputting a terminal address capture signal of said opposite communication party (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44); b. destination terminal address request message output

means for receiving said opposite communication party's name, broadcasting as said transmission packet a message requesting the correspondence relationship between said opposite communication party's name and said opposite communication party's terminal to a communication medium in which a connection network of said mobile terminal itself configures an ad hoc network, and outputting a timer start-up signal (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where Examiner takes official notice that timers are well known in the art to measure a time-out period; c. a timer for starting measuring a predetermined period of time in response to said timer start-up signal, ceasing measurement of said predetermined period of time when a terminal address capture signal of said opposite communication party is received during measuring said predetermined period of time, and outputting a time-out signal representing a timeout when the measurement of said predetermined period of time ends (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where Examiner takes official notice that timers are well known in the art to measure a time-out period; d. terminal address non-capture detection means for outputting a terminal address non-capture signal representing that a terminal address corresponding to said opposite communication party's name cannot be captured, when said time-out signal is received (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where Examiner takes official notice that timers are well known in the art to measure a time-out period; e. a control circuit for outputting a switch control pulse that selects said terminal address non-capture signal when said time-out signal is input and selects a terminal address capture signal of said opposite communication party when a terminal address capture signal of said opposite communication party is input (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where Examiner takes official notice that timers are well known in the art to measure a

time-out period; f. a switch for selectively outputting said terminal address non-capture signal or said terminal address capture signal of said opposite communication party, based on said switch control pulse (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where Examiner takes official notice that timers are well known in the art to measure a time-out period; g. destination terminal address request message detection means for detecting said destination terminal address request message in response to said receive packet and then outputting said destination address message transmission request signal when said destination terminal address request message requests a terminal address to the name of said mobile terminal itself (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44); and h. destination terminal address message transmission means for broadcasting as said transmission packet said destination terminal address message containing its own terminal address to a communication medium in which a connection network of said mobile terminal configures an ad hoc network, when said destination address message transmission request signal is input (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44).

15. Regarding claim 9, referring to claim 2, Brewer in view of Sharony discloses that the mobile management means comprises: a. network advertisement request message transmission means for detecting said infrastructure network advertisement message or said ad hoc network advertisement message containing a network address of a network to which said mobile terminal is connected, in response to said receive packet, detecting that said mobile terminal has been moved to a different network when said infrastructure network advertisement message or said ad hoc network advertisement message cannot be received for a predetermined period of time, and transmitting said infrastructure network advertisement message or said ad hoc network

Art Unit: 2665

advertisement request message requesting the network address of said network (Brewer: col. 9, lines 21-35 and col. 9, lines 39-52 and Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44) where a time-out is implicit; and b. ad hoc network advertisement means for receiving said receive packet when a network to which said mobile terminal is connected is an ad hoc network, and transmitting said ad hoc network advertisement message representing the presence of said ad hoc network in cooperation with another mobile terminal connected to said ad hoc network (Sharony: col. 5, line 36-col. 6, line 14 and col. 6, lines 33-44).

### Allowable Subject Matter

- 16. Claim 4 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims. The prior art does not disclose or fairly suggest steps (c)-(k).
- 17. Claim 8 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims. The prior art does not disclose or fairly suggest steps (c)-(h).
- 18. Claim 10 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims. The prior art does not disclose or fairly suggest steps (c)-(i).

#### Conclusion

19. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Belanger et al (USPN 5,729,680) see col. 2, lines 9-28; col. 4, line 62-col. 5, line 15; col. 10, lines 46-col. 11, line 14; col. 13, lines 9-25; col. 13, lines 36-50; col. 25, line 50-col. 26, line 37; and col. 26, lines 56-65 which pertains to a wireless network where a mobile unit can

Art Unit: 2665

roam from an infrastructure to an ad hoc network. Perkins (USPN 5,412,654) see entire document which pertains to exchanging routing information in an ad hoc network. Messenger (USPN 5,276,680) see entire document which pertains to registering a wireless device in an infrastructure network.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Daniel J. Ryman whose telephone number is (571)272-3152. The examiner can normally be reached on Mon.-Fri. 7:00-4:30 with every other Friday off.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Huy Vu can be reached on (571)272-3155. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Daniel J. Ryman
Examiner
Art Unit 2665

SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600